

Datum: 19.11.2025

OIB: HR13160244056
Telefon: +385 31 328 956
E-mail: info@hardware.hr
WWW: www.hardware.hr



(slika je simbolična)

TP-Link AC750 bežični pojačivač dometa (Range Extender), Dual Band 433Mbps(5GHz)/300Mbps(2.4GHz), 802.11ac/a/b/g/n, 3x interna antena

Kategorija: [TP-Link - WIRELESS](#)
Dobavljivost: **predviđena dostava 25.11.2025**
Šifra: **166873**

Cijena: 24,00€

Brend: TP-LINK
Zaliha: Na skladištu

Kratak opis

BOOST YOUR Wi-Fi NETWORK TO COVER HARD-TO-REACH AREAS - Place the RE190 between your wireless router and wireless devices, expanding Wi-Fi coverage while eliminating Wi-Fi dead zones - Enjoy a seamless wireless network throughout your home or office - The dual bands Wi-Fi up to 750Mbps not only help extend to 2.000 sq.ft. (185 m2), but also make good use of your high ISP speed - ideal for HD video streaming, online gaming and other bandwidth-intensive tasks AC750 Wi-Fi FOR COMPATIBLE CONNECTIONS - The RE190s Wireless AC technology create stronger Wi-Fi connections across your home. Work with any standard router or access point, making it convenient to provide wide, non-dropping Dual Band Wi-Fi to multiple devices ONE KEY CONNECTION - Press the WPS button on your router and RE button on your RE190 within 2 minutes to easily connect to the network - Once connected with an existing router, you can simply relocate the RE190 at any location for the best signal strength SMART SIGNAL INDICATOR - Smart signal lights indicate the signal strength received from the existing router - Read the lights to find the best location for your RE190 **Features** - Boosts wireless signal to previously unreachable or hard-to-wire areas flawlessly - Compatible with 802.11 b/g/n and 802.11ac Wi-Fi devices - Dual band speeds up to 750Mbps - Miniature size and wall-mounted design make it easy to deploy and move flexibly **Specifications** **HARDWARE FEATURES** - Button: WPS Button, RESET Button - Power Consumption: 7.0W - Dimensions: 110.0x65.8x38.8 mm - Antenna: 3 Omni-directional Antennas **WIRELESS FEATURES** - Wireless Standards: IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz - Frequency: 2.4GHz and 5GHz - Signal Rate: 300Mbps at 2.4GHz, 433Mbps at 5GHz - Reception Sensitivity: * 5GHz: 11a 6Mbps: -94dBm, 11a 54Mbps: -78dBm 11ac HT20 MCS0: -94dBm, MCS8: -73dBm 11ac HT40 MCS0: -91dBm, MCS9: -65dBm 11ac HT80 MCS0: -88dBm, MCS9: -62dBm - 2.4GHz: 11g 54Mbps: -78dBm, 11n HT20: -75dBm 11n HT40: -73dBm - Transmit Power: CE: <20dBm(2.4GHz), <23dBm(5.15GHz - 5.35GHz); <30dBm(5.47GHz - 5.725GHz) - Wireless Functions: WMM, Short GI, High Speed, WPS - Wireless Security: WEP, WPA/WPA2-PSK encryptions **OTHERS** - Certification: CE, RoHS - Package Contents: Range Extender RE190, Quick Installation Guide - System Requirements: * Microsoft Windows 98SE, NT, 2000, XP, Vista or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux * Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser - Environment: * Operating Temperature: 0C - 40C * Storage Temperature: -40C - 70C * Operating Humidity: 10% - 90% RH * Storage Humidity: 5% - 90% RH