

Datum: 19.11.2025

OIB: HR13160244056
Telefon: +385 31 328 956
E-mail: info@hardware.hr
WWW: www.hardware.hr



(slika je simbolična)

TP-Link AX3000 bežični pojačivač dometa (Wi-Fi 6 Range Extender/AP), Dual Band 574Mbps/2402Mbps (2.4GHz/5GHz), 802.11a/n/ac/ax/b/g/n, 1xG-LAN, 2xinterna antena

Kategorija: [TP-Link - WIRELESS](#)

Dobavljalivost: **predviđena dostava 25.11.2025**

Šifra: **167388**

Cijena: 82,00€

Brend: TP-LINK
Zaliha: Na skladištu

Kratak opis

Dual Band WiFi 6 - Separates 5 GHz (2402 Mbps) and 2.4 GHz (574 Mbps) WiFi bands for faster speeds and greater capacity with the latest technology Uninterrupted Streaming - Easily create a TP-Link OneMesh network for seamless whole home WiFi coverage AP Mode - Create a new WiFi access point through the Gigabit Ethernet port to enhance your wired network with WiFi capability Adaptive Path Selection - Automatically choosing the fastest connection path to the router App Control - Easy Setup and management with your network using the TP-Link Tether app **Specifications** WIRELESS - Working Modes: Range Extender / Access Point HARDWARE FEATURES - Ports: 1 Gigabit Ethernet Port - Button: WPS Button, Reset Button - Input Power: 100-240V~50/60Hz - Power Consumption: 11.2W - Dimensions (W x D x H): 78*36*149 - Antenna: 2 Internal Antennas WIRELESS FEATURES - Wireless Standards: IEEE 802.11a/n/ac/ax 5GHz, IEEE 802.11b/g/n/ax 2.4GHz - Frequency: 2.4GHz and 5GHz - Signal Rate: 574 Mbps at 2.4GHz, 2402 Mbps at 5GHz - Working Modes: Range Extender / Access Point - Reception Sensitivity - 5GHz: • 11a 6Mbps: -97dBm • 11a 54Mbps: -78dBm • 11ax HE20 MCS0:-97dBm • 11ax HE20 MCS11:-66dBm • 11ax HE40 MCS0:-94dBm • 11ax HE40 MCS11:-63dBm • 11ax HE80 MCS0:-91dBm • 11ax HE80 MCS11:-61dBm • 11ax HE160 MCS11:-59dBm 2.4GHz: • 11g 6Mbps:-96dBm • 11g 54Mbps:-78dBm • 11ax HE20 MCS0: -96dBm • 11ax HE20 MCS11: -65dBm • 11ax HE40 MCS0: -93dBm • 11ax HE40 MCS11: -63dBm - Wireless Functions • Enable/Disable Wireless Radio • DFS (the latest firmware and hardware version is required) • Access Control • LED Control • Power Schedule • Wi-Fi Coverage - Wireless Security: WEP, WPA, WPA2, WPA3 - Transmission Power: CE: 2.4GHz ?16dBm, 5GHz ?21dBm - Mesh Technology: EasyMesh-Compatible OTHERS - Certification: CE, RoHS - Package Contents: • Wi-Fi Range Extender RE700X • Quick Installation Guide - System Requirements • Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux • Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser - Environment • Operating Temperature: 0?~40? (32? ~104?) • Storage Temperature: -40?~70? (-40? ~158?) • Operating Humidity: 10%~90% non-condensing • Storage Humidity: 5%~90% non-condensing