

Datum: 19.11.2025

OIB: HR13160244056
Telefon: +385 31 328 956
E-mail: info@hardware.hr
WWW: www.hardware.hr



(slika je simbolična)

**TP-Link bežična pristupna točka
vanjska (AP) 300Mbps (5.0GHz),
802.11a/n, podrška za Pasive PoE,
1xLAN, IP65, Pharos MAXtream, 29dBi
usmjeriva antena**

Kategorija: [TP-Link - WIRELESS](#)
Dobavljivost: **predviđena dostava 25.11.2025**
Šifra: **166842**

Cijena: 84,00€

Brend: TP-LINK
Zaliha: Na skladištu

Kratak opis

- Up to 300Mbps on 5GHz wireless data rates - 23dBi high-gain directional 2x2 MIMO antenna and a dedicated metal reflector, ideal for long-distance application - Excellent beam directivity, improved latency and noise cancellation - Innovative snap-lock parts make for fast assembly and a sturdy structural design keeps CPE610 stable even in strong winds - Durable IP65 weatherproof enclosure along with 15 kV ESD and 6 kV lightning protection ensures all-weather suitability - TP-Link Pharos MAXtream TDMA technology improves throughput, capacity and latency performance - Pharos Control gives administrators a free, centralized management system - Passive PoE supports to allow flexible deployment and convenient installation

Specifications

HARDWARE FEATURES - Processor: Qualcomm 560MHz CPU, MIPS 74Kc - Memory: 64MB DDR2 RAM, 8MB Flash - Interface: * 1 10/100Mbps Shielded Ethernet Port (LAN/POE) * 1 Reset Button - Power Supply: * Passive Power over Ethernet via LAN (+4, 5pins; -7, 8pins) * Voltage range: 16-27VDC - Dimensions (WxDxH): 366x280x207 mm (14.4"x11.0"x8.1") - Antenna Gain: 23dBi - Antenna Beamwidth: 9° (Azimuth), 7° (Elevation) - Protection: * 15KV ESD Protection * 6KV Lightning Protection - Enclosure: * Material: Outdoor PC stabilized plastic * Weatherproof: IP65 water and dust proof design

WIRELESS FEATURES - Wireless Standards: IEEE 802.11a/n - Proprietary Protocol: TDMA Mode (with Pharos MAXtream enabled) - Wireless Speeds: * Up to 300Mbps (40MHz, Dynamic) * Up to 144.4Mbps (20MHz, Dynamic) * Up to 72.2Mbps (10MHz, Dynamic) * Up to 36.1Mbps (5MHz, Dynamic) - Frequency: 5.15 - 5.85GHz - Transmit Power: Max. 25dBm (Adjustable power by 1dBm)

SOFTWARE FEATURES - Network Configuration: * WAN: Static/Dynamic/PPPoE/L2TP/PPTP * LAN: Static/Dynamic/DHCP * Forwarding: ALG/UPnP/Virtual Server/Port Trigger * Security: SPI Firewall/ Ping Forbidden/DoS Protection * Access Control * Static Routing * Bandwidth Control * IP & MAC Binding - Wireless Configurations: * Pharos MAXtream TDMA Technology * Selectable Channel Width: 5/10/20/40MHz * Auto Channel Selection * Transmit Power Control * Dynamic Frequency Selection(DFS) * WDS Enable/Disable * Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, * 64/128/152-bit WEP Encryption * SSID Broadcast Enable/Disable * Multi-SSID with VLAN Tagging(AP Mode only) * Distance/ACK Timeout Setting * Wireless MAC Address Filter * Wireless Advanced: * Beacon Interval/RTS Threshold/Fragmentation Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia - Management: * Discovery and Remote Management via Pharos Control application * HTTP/HTTPS Web-based management * System log * SNMP Agent(v2c) * Ping Watch Dog * Dynamic DDNS * SSH Server - System Tools: * Indicators: Signal Strength/Noise/Transmit CCQ/CPU/Memory * Monitors: Throughput/Stations/Interfaces/ARP/Routes/WAN/DHCP * Spectrum Analyzer * Speed Test * Ping * Traceroute - System-level Optimizations: * Optimized IGMP Snooping/Proxy for multicast applications * Hardware watch dog

POE ADAPTER FEATURES - Dimensions (WxDxH): 85.8x43.9x29.7 mm - Interfaces: * 1 AC Jack with Earth Ground * 1 10/100Mbps Shielded Ethernet Port (Power + Data) * 1 10/100Mbps Shielded Ethernet Port (Data) - Button: Remote Reset Button - Power Status LEDs: Green - Input: 100-240VAC, 50/60Hz - Output: * 24VDC, 0.6A Max * +4, 5pins; -7, 8pins. (Support up to 60m Power over Ethernet) - Efficiency: >84.29% - Certifications: CE/FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark OTHERS - Certification: CE, FCC, IC, RoHS, IP65 - Package Contents: Outdoor Wireless CPE, 24V 0.5A Passive PoE Adapter, Pole Mounting Straps, AC Power Cord, Installation Guide - System Requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux * Note: We recommend you to use one of following Web browsers for an improved user experience: Google Chrome, Safari, and Firefox. IE browsers are not recommended - Environment: * Operating Temperature: -40C - 70C (-40F - 158F) * Storage Temperature: -40C - 70C (-40F - 158F) * Operating Humidity: 10% - 90% non-condensing * Storage Humidity: 5% - 95% non-condensing