

Datum: 19.11.2025

INFOS PROMOTION d.o.o. Kninska 24, 31000 Osijek, Hrvatska

OIB: HR13160244056 **Telefon:** +385 31 328 956

E-mail: info@hardware.hr WWW: www.www.hardware.hr



TP-Link VIGI NVR1008H mrežni video snimač 8 kanala, H.265, 5MP, 1×SATA, VGA/HDMI, 2×USB2.0, Vigi app

Kategorija: TP-Link - VIDEO NADZOR

Dobavljivost: predviđena dostava 25.11.2025

Šifra: **166906**

Cijena: 96,00€

(slika je simbolična)

Brend: TP-LINK Zaliha: Na skladištu

Kratak opis

- 24/7 Continuous Recording: Automatically stores up to 10 TB of footage from connected cameras to secure your data for quick, convenient access - 8-Channel Real-Time Live View: Sharp image definition up to 5MP and an 8 channel display ensures you capture every detail, from every angle - 4-Channel Simultaneous Playbackt: Replay the feed from up to 4 cameras at the same time, increase replay speed, and find events in the video schedule to easily review footage - Remote Monitoring: Dedicated VIGI app is developed for remote monitoring, providing ease and convenience - H.264+: Without using any extra bandwidth, your camera transmits compressed crystalclear video to save disk space, ease network loads, and reduce monitoring costs without sacrificing image quality - Onvif Ensure Compatibility: Easily add IPCs from VIGI and other brands to establish a powerful and varied network thanks to barrier-free compatibility - 1 HDD Interface (up to 10 TB)?: Stores up to 10 TB (720 days of video) on a SATA hard drive, keeping your data storage secured locally - Two-Way Audio: With voice intercom support, carry two-way conversations while watching your feed from anywhere. Suitable for management -80 Mbps Video Access Bandwidth: High video access bandwidth ensures your NVR connects more cameras with high resolution. Based on laboratory testing using VIGI cameras, VIGI NVR can connect up to eight 4MP cameras Specifications NETWORK - Protocol: TCP/IP, DHCP, DNS, NTP, UPnP - Incoming Bandwith: 80 Mbps - Outgoing Bandwidth: 60 Mbps GENERAL - Operating Temperature: -10C to 55C - Chassis: 1U Chassis - Dimensions (H×W×D): 246.2×148.2×42.6 mm - Weight: 578.5 g - External Power Supply: 12V DC, no more than 18 W - Power Consumption: * 4.25 W (without disk) * 13.10 W (with disk) VIDEO/IMAGE - Video Input: 8-Channel IP Video Input, up to 5 MP Resolution - Video Output: * Recording Resolution: 5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF * HDMI/VGA Output Resolution: 1920×1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1680×1050/60Hz, 1440×900/60Hz DECODING -Decoding Format: H.264+/H.264 - Live View/Playback Resolution: 5 MP/ 4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF -Synchronous Playback: 4 Channel - Capability: 1-ch @ 5MP, 2-ch @ 2MP, 4-ch @ 720p HARD DISK - SATA: 1× SATA Interface - Capacity: Up to 10 TB INTERFACES - Network Interface: 1× RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface - USB Interface: 2x USB 2.0