

Datum: 19.11.2025

OIB: HR13160244056
Telefon: +385 31 328 956
E-mail: info@hardware.hr
WWW: www.hardware.hr

Ubiquiti UniFi Managed 8-port Gigabit Switch, 6xGbE PoE+, 2xGbE PoE++, 2x10G SFP+, 120W (USW-Pro-8-PoE)



Kategorija: [UBIQUITI - UniFi Routing & Switching](#)
Dobavljivost: **predviđena dostava 25.11.2025**
Šifra: **167240**

Cijena: 369,00€

(slika je simbolična)

Brend: UBIQUITI
Zaliha: Na skladištu

Kratak opis

- An 8-port, Layer 3 switch with PoE+ and PoE++ output.
Features - (6) GbE PoE+ ports - (2) GbE PoE++ ports - (2) 10G SFP+ ports - 120W total PoE availability
Specifications
Mechanical - Dimensions: 200 x 248 x 44 mm (7.9 x 9.8 x 1.7") - Weight: 2.1 kg (4.6 lb) - Enclosure materials: Polycarbonate, metal - Mount material: Polycarbonate
Hardware - Management interface: Ethernet In-Band - Networking interface • (8) GbE RJ45 ports • (2) 10G SFP+ ports - PoE interface • (6) PoE/PoE+ (Pins 1, 2+; 3, 6-) • (2) 60W PoE++ (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-) - Total non-blocking throughput: 28 Gbps - Switching capacity: 56 Gbps - Power method: Universal input, 100—240V AC, 2A Max. - Power supply: AC/DC, internal - Supported voltage range: 100—240V AC - Max. power consumption: 30W (Excluding PoE output) - Total available PoE: 120W - Max. PoE wattage per port by PSE • PoE: 15W • PoE+: 30W • PoE++: 60W - Voltage range PoE mode • PoE: 44—57V • PoE+: 50—57V • PoE++: 50—57V - LCM display: (1) 1.3" touchscreen - LEDs: RJ45 ports: link/activity - Button: Factory reset - Ambient operating temperature: -5 to 45° C (23 to 113° F) - Ambient operating humidity: 10 to 90% noncondensing - Certifications: CE, FCC, IC
Switching Features - Layer 2 features • IGMP snooping • STP / RSTP with priorities and port-level disable • Port isolation • Storm control • Voice VLAN • Port mirroring • LACP port aggregation • Multicast / broadcast rate limiting • MAC address blocking • Flow control • 802.1X control • Jumbo frames • Proprietary loop protection • DHCP snooping / guarding • Egress rate limit • LLDP-MED • Port restricted by MAC • Device isolation with ACLs - Layer 3 features • DHCP for locally-managed networks • DHCP relay • Inter-VLAN routing between networks on same switch • Static routing between local networks
Application Requirements - UniFi Network: Version 7.5.176 and later