

Datum: 05.03.2026

OIB: HR13160244056
Telefon: +385 31 328 956
E-mail: info@hardware.hr
WWW: www.hardware.hr



**Xilence 400W Performance C, ATX
2.3.1, aktivan PFC, 1xPCIe, 3xSATA,
20+4-pina, 120mm ventilator, crno**

Kategorija: [Napajanja](#)

Dobavljivost: **Nema proizvoda na skladištu**

Šifra: **179127**

Cijena: 41,00€

(slika je simbolična)

Kratak opis

- The new Xilence Performance C series is focusing on the essentials. Designed for office and home computers, the new Performance C series delivers stable voltages with high efficiency (ErP2014). This guarantees a considerably low fan noise. Four built-in safety circuits ensure safe operation at all times.

Features

- Extremely silent cooling: large 120mm fan
- Excellent air flow design for a better heat dissipation
- Following safety design:
 - * Over Voltage Protection (OVP)
 - * Under Voltage Protection (UVP)
 - * Short Circuit Protection (SCP)
 - * Over Load Protection (OLP)
- Low stand-by consumption
- Complies with ErP2014 norm

Specifications

General data

- Peak Power (W): 400
- Form factor ATX 12V: Version 2.31
- Voltage (Vac): 200 - 240
- Model: Performance C | XP400R6
- Frequency (Hz): 50
- Input current (A): 6.3
- PFC: Active

Output

- +3.3V (A): 15
- +5V (A): 12
- +12V1 (A): 13
- -12V (A): 0.3
- +5Vsb (A): 3.0
- Max. combined power 12V (W): 228
- Max. combined power 3.3V + 5V (W): 103
- +12V2 (A): 13

Fan / Cooling technology

- Bearing technology: FDB
- Fan size (mm): 120

Protection

- OCP (over current protection): No
- OVP (over voltage protection): Yes
- UVP (under voltage protection): Yes
- SCP (short circuit protection): Yes
- OTP (over temperature protection): No
- OPP (over power protection): Yes

Eco / Efficiency

- 80PLUS certification: No
- Efficiency (%) at 230V, 20% load: 82.64
- Efficiency (%) at 230V, 50% load: 85.43
- Efficiency (%) at 230V, 100% load: 82.55

Environmental directives

- ErP: Yes
- WEEE: Yes
- RoHS: Yes

Cable management / Connectors

- Modular cable management: No
- Cable length to mainboard (mm): 450
- Cable length to first connector (mm): 400
- Maximum cable length (mm): 550
- Sleeved cables: No
- No. of cables: 5
- ATX-Motherboard (20+4-pin): 1
- P4+4 (CPU): No
- P8 (CPU): 1
- PCI-E 6-pin (GPU): 1
- PCI-E 6+2-pin (GPU): No
- PATA 4-pin: 1
- SATA 15-pin (HDD, Drives): 3
- FDD (Floppy): No

Logistics data, RRP

- Range Performance C
 - Article number: XN041
 - Dimensions, package (L x W x H), (mm): 230 x 165 x 100
 - Gross weight, package (kg): 1.42
 - Pieces per packaging unit: 10
 - Dimensions, shipping box (L x W x H), (mm): 510 x 350 x 250
 - Gross weight, shipping box (kg): 14.88
-