

Datum: 02.06.2026

OIB: HR13160244056  
Telefon: +385 31 328 956  
E-mail: [info@hardware.hr](mailto:info@hardware.hr)  
WWW: [www.hardware.hr](http://www.hardware.hr)



**Xilence 650W Gaming, ATX 2.52v 80+  
GOLD, aktivan PFC, 3×PCIe, 6×SATA,  
120mm ventilator, crno**

Kategorija: [Napajanja](#)  
Dobavljivost: **predviđena dostava 05.06.2026**  
Šifra: **180369**

**Cijena: 85,00€**

(slika je simbolična)

## Kratak opis

- The Gaming GOLD Series is a PC power supply series with a fixed cable harness, as well as a 750W ARGB variant
- The noble design with its black powder coating, the 120mm silent, black or transparent fan and the fan grille emphasizes the valuable character of this series
- The maximum voltage stability and the six integrated safety circuits ensure safe operation even in heated workflows or gaming sessions
- The power supplies are suitable for the highest demands in gaming, multi-media application and streaming areas and have low power consumption during these intensive phases
- The power supplies achieve the 80+ GOLD requirements

### Features

- Whisper-quiet cooling: Large 120mm fan\*
- Excellent airflow design for improved heat dissipation
- With the following safety equipment:
  - \* OVP (overvoltage protection)
  - \* UVP (Undervoltage Protection)
  - \* SCP (short circuit protection)
  - \* OLP (overload protection)
  - \* OTP (over temperature protection)
  - \* OCP (overcurrent protection)
- Low standby power consumption
- High energy

### Technical data

- Continuous power (W): 650
- Form factor ATX 12V: Version 2.52v
- Voltage (Vac): 200-240V
- Mode: Gaming | XP650R12
- Frequency (Hz): 50Hz-60Hz
- Input current (A) 6.3
- PFC: active

### Output

- \* +3.3V (A): 20
- \* +5V (A) : 20
- \* +12V1 (A): 54.1
- \* -12V (A): 0.3
- \* +5Vsb (A): 3
- \* Max. combined power 12V (W): 650
- \* Max. combined power 3.3V + 5V (W): 100
- \* +12V2 (A): Yes

### Fan / Cooling technology

- Bearing technology: Hydro Bearing
- Fan size (mm): 120

### Protection

- OCP (over current protection): Yes
- OVP (over voltage protection): Yes
- UVP (under voltage protection): Yes
- SCP (short circuit protection): Yes
- OTP (over temperature protection): Yes
- OPP (over power protection): Yes

### Eco / Efficiency

- 80PLUS certification: meet 80+ Gold
- Efficiency (%) at 230V, 20% load: 90
- Efficiency (%) at 230V, 50% load: 93
- Efficiency (%) at 230V, 100% load: 92

### Environmental directives

- ErP: Yes
- WEEE: Yes
- RoHS: Yes

### Cable management / Connectors

- Modular cable management: -
  - Cable length to mainboard (mm): 550
  - Cable length to first connector (mm): 550
  - Maximum cable length (mm): 600
  - Sleeved cables: Yes
  - No. of cables: -
  - ATX-Motherboard (20+4-pin): -
  - P4+4 (CPU): 2
  - P8 (CPU): 1
  - PCI-E 6-pin (GPU): -
  - PCI-E 6+2-pin (GPU): 3
  - PATA 4-pin: -
  - SATA 15-pin (HDD, Drives): 6
  - FDD (Floppy): -
-