

Datum: 02.06.2026

OIB: HR13160244056
Telefon: +385 31 328 956
E-mail: info@hardware.hr
WWW: www.hardware.hr



**Xilence 750W Gaming, ATX 2.52 80+
BRONZE, aktivan PFC, 2×PCIe,
6×SATA, 20+4-pina, 120mm
ventilator, crno**

Kategorija: [Napajanja](#)
Dobavljivost: **predviđena dostava 05.06.2026**
Šifra: **180380**

Cijena: 70,00€

(slika je simbolična)

Brend: XILENCE
Zaliha: Na skladištu

Kratak opis

- The new successful Gaming series combines high performance with a low noise level and high efficiency
- The new DC/DC technology guarantees for increased efficiency and a maximum tension stability even during excessive gaming
- Thanks to this high efficiency and the associated 80+ BRONZE certification high electricity costs are now a thing of the past
- Six integrated safety circuits provide for an all-time safe operation and the sleeved main cable harness ensures order in the PC case

Features

- Extremely silent cooling: large 120mm fan
- semi-modular cable management
- Excellent air flow design for a better heat dissipation
- Full safety design:
 - * OVP (Over Voltage Protection)
 - * UVP (Under Voltage Protection)
 - * SCP (Short Circuit Protection)
 - * OPP (Over Power Protection)
- Low stand-by consumption
- High energy efficiency: 80+ BRONZE certified (complies with ErP2014 norm)
- Active-PFC

Technical data

- Continuous power: 750W
- Form factor ATX 12V: Version 2.52
- Voltage: 200 - 240 Vac
- Frequency: 50Hz
- Input current: 10A
- PFC: active

OUTPUT

- * +3.3V: 20A
- * +5V: 20A
- * +12V1: 62.5A
- * -12V: 0.3A
- * +5Vsb: 3.0A
- Max. combined power 12V: 750W
- Max. combined power 3.3V + 5V: 100W

FAN / COOLING TECHNOLOGY

- Bearing technology: FDB
- Fan size: 120mm

PROTECTION

- OVP (over voltage protection): Yes
- UVP (under voltage protection): Yes
- SCP (short circuit protection): Yes
- OPP (over power protection): Yes

ECO / EFFICIENCY

- 80PLUS certification: Bronze

ENVIRONMENTAL DIRECTIVES

- ErP: Yes
- WEEE: Yes
- RoHS: Yes

CABLE MANAGEMENT / CONNECTORS

- Modular cable management: Yes
 - Cable length to mainboard: 500mm
 - Cable length to first connector: 450mm
 - Maximum cable length: 750mm
 - No. of cables: 7
 - ATX-Motherboard (20+4-pin): 1
 - P4+4 (CPU): 1
 - PCI-E 6+2-pin (GPU): 2
 - PATA 4-pin: 3
 - SATA 15-pin (HDD, Drives): 6
-