

Datum: 03.06.2026

OIB: HR13160244056  
Telefon: +385 31 328 956  
E-mail: [info@hardware.hr](mailto:info@hardware.hr)  
WWW: [www.hardware.hr](http://www.hardware.hr)



**Xilence 750W Performance X+, ATX  
3.0 80+ GOLD, polumodularno, aktivan  
PFC, 4×PCIe, 6×SATA, 20+4-pina,  
140mm ventilator, crno**

Kategorija: [Napajanja](#)  
Dobavljivost: **predviđena dostava 09.06.2026**  
Šifra: **180388**

**Cijena: 117,00€**

(slika je simbolična)

## Kratak opis

- The semi-modular power supplies of the X+ series are capable of absorbing high load peaks above the normal rated power in the shortest possible time and comply with Intel's Design Guide 3.0. Thus, the power supplies are ideally suited for driving the latest and most powerful gaming graphics cards with PCI Express 5 specifications. An 80+ Gold certification confirms a high efficiency and energy efficiency of this power supply series. Six different protection circuits (OCP, OVP, UVP, SCP, OPP, OTP) ensure safe operation even in heated gaming sessions. The fans of the ATX 3.0 power supplies run with Fluid Dynamic Bearing technology and are very quiet. In addition, they convince with an extremely long durability and their excellent cooling performance. All of these specifications make the affordable Performance X+ series ideal for use with the latest gaming PC systems.

### Features

- 12VHPWR (PCIe Gen 5.0)
- Extremely silent cooling: large 140mm fan
- Excellent air flow design for a better heat dissipation
- Modular cable management
- Following safety design:
  - OVP (Over Voltage Protection)
  - UVP (Under Voltage Protection)
  - OCP (Over Current Protection)
  - OTP (Over Temperature Protection)
  - SCP (Short Circuit Protection)
  - OLP (Over Load Protection)
- Low stand-by consumption
- high energy efficiency: 80+ GOLD® and EcoPSU certified (complies with ErP2014 norm)
- Active-PFC

### Specifications

#### General data

- Form factor: ATX 12V Version 3.0
- Model: Performance X+ | XP7550MR9.2
- PFC: Active

#### Output

- +3.3V (A): 20.0A
- +5V (A): 20.0A
- +12V1 (A): 62.5A
- 12V (A): 0.3A
- +5Vsb (A): 3.0A

#### Fan / Cooling technology

- Fan size (mm): 140

#### Protection

- OCP (over current protection): Yes
- OVP (over voltage protection): Yes
- UVP (under voltage protection): Yes
- SCP (short circuit protection): Yes
- OTP (over temperature protection): Yes
- OPP (over power protection): Yes

#### Eco / Efficiency

- 80PLUS certification: Gold
- Efficiency (%) at 230V, 20% load: 91%
- Efficiency (%) at 230V, 50% load: 93%
- Efficiency (%) at 230V, 100% load: 92%

#### Environmental directives

- ErP: Yes
- WEEE: Yes
- RoHS: Yes

#### Cable management / Connectors

- Modular cable management: Yes
- Sleeved cables: Yes
- P4+4 (CPU): 1
- P8 (CPU): 1
- PCI-E 6-pin (GPU): 1
- PCI-E 6+2-pin (GPU): 3
- SATA 15-pin (HDD, Drives): 6

#### Logistics data, RRP

- Range: Performance X+
  - Article number: XN173
-